

Cisco TelePresence TX1310

Product Overview

The Cisco TelePresence® TX1310 extends the experience pioneered by Cisco's fully immersive three-screen solutions to smaller general purpose conferencing spaces. The TX1310 delivers an immersive experience on a single-screen system that enhances team collaboration across the table and around the globe (Figure 1).

Figure 1. Cisco TelePresence System TX1310



The TX1310 65, features a 65-inch screen, crisp video resolution of up to 1080p60 (1080 pixels displayed at 60 frames per second), high-definition 1080p30 content sharing, premium audio quality, and the convenience of features such as “one button-to-push” calling. The TX1310 delivers the high-quality experience expected of Cisco® immersive telepresence rooms. With an innovative combination of triple-camera cluster and voice-activated switching technology, the TX1310 enables up to six participants to have a face-forward seat at the virtual table through a single video stream. Integrated audio conferencing and presentation-sharing capabilities make this solution a powerful team telepresence solution that enhances collaboration in many ways.

The TX1310 65 is designed for medium- and larger-sized conference rooms, using the existing table in the room, (Figure 2) to help customers extend high quality immersive experience to their larger workforce.

Figure 2. Cisco TelePresence TX1310 65



Applications

The Cisco TelePresence TX1310 is ideal for multipoint group meetings such as operational reviews, status update meetings, and customer presentations. It also enables geographically dispersed teams to collaborate in one-on-one meetings and general working sessions.

Total Solution

The TX1310 is part of the broad portfolio of Cisco TelePresence systems offering immersive, multipurpose, and personal endpoints to meet the needs of organizations of all sizes. Cisco TelePresence solutions power the new way of working where everyone, everywhere can be more productive through face-to-face collaboration.

Features and Benefits

- Platform designed to work with advanced collaboration features.
- “One-button-to-push” and ad-hoc calling is even easier with a simple and intuitive Touch 12 user interface.
- Triple-camera cluster and voice-activated switching maximize utility and limit bandwidth usage.
- Resolution of up to 1080p60 on a premium 65-inch screen helps ensure true-to-life visual connection.
- Presentation-in-picture allows for easy content sharing, and a connector is available for adding a dedicated auxiliary display.
- An optional audio-conferencing capability maximizes the solution utility.
- The solution offers multiuse capabilities such as laptop sharing or digital signage when not in a telepresence call.
- An integrated lighting assembly eliminates facial shadows and provides natural-looking video.
- Front speakers provide superior audio.
- Any-to-any interoperability is possible with standard- and high-definition video endpoints.

Product Specifications

Tables 1 through 3 list specifications for the Cisco TelePresence TX1310 65.

Table 1. Product Specifications

Specification	Description
Product compatibility	<ul style="list-style-type: none"> • Cisco Unified Communications Manager 8.5.2 & 8.6.2 or later • Cisco TelePresence Multipoint Switch 1.8 or later • Cisco TelePresence Manager 1.8 or later
Software compatibility	<ul style="list-style-type: none"> • Cisco TelePresence System Software Version 1.9 or later
User interface	<ul style="list-style-type: none"> • Cisco TelePresence Touch Screen (12-in.)
Cisco TelePresence high-definition camera	<ul style="list-style-type: none"> • Complementary metal oxide semiconductor (CMOS) 1/3-inch sensor • CS-mount lens • 1080p, 30 or 60 frames per second (fps) • Minimum illumination: 300 lux • Manual focus
Physical dimensions (H x W x D)	<ul style="list-style-type: none"> • Minimum room dimensions: 8 x 18 x 13 ft (243.84 x 548.64 x 396.24 cm) • Wall-mounted: 77.4 x 80 x 7.5 in. (196.60 x 203.20 x 19.05 cm)
Weight	Cisco TelePresence TX1310 65: Maximum 600 lb (272.16 kg)
Power	Cisco TelePresence TX1310 65: Maximum 1440W, typical 1216W, standby 240W
Temperature range	Operating: 41 to 95°F (5 to 35°C) Relative humidity: 10 to 95% (noncondensing)
Firmware upgrades	Downloadable from Cisco Unified Communications Manager
Regulatory compliance	<ul style="list-style-type: none"> • CE marking • UL/CSA/IEC/EN/AS/NZS/60950 • 47CFR Part 15 Class A • CISPR22/EN55022 Class A

Table 2. Video and Audio Specifications

Specification	Description
Bandwidth consumption	3 to 4 Mbps (1080p) or 1.5 to 3 Mbps (720p) for IP quality-of-service (QoS) connections recommended
Video standards	H.264, Telepresence Interoperability Protocol (TIP)
Video frame rate	Video frame rate 60fps using H.264
Data and graphics frame rate	TX1310 65 graphics sharing at 5 fps (default configuration) & 30fps (at no additional cost)
Native National Television Standards Committee (NTSC)	720p and 1080p
Live video resolution	1920 x 1080 Native
H.264 interoperability	Using Common Intermediate Format (CIF), G.722, and G.711 with Cisco Unified Videoconferencing 3500 Series platforms
Audio standards	G.711, G.722, and AAC-LD (22 kHz)
Audio features	Cisco Dynamic Echo Cancellation

Table 3. Network, Security, and Management Specifications

Specification	Description
Protocols	Cisco Discovery Protocol, Session Initiation Protocol (SIP), IP, Dynamic Host Configuration Protocol (DHCP), Secure Shell (SSH) Protocol, 802.1p/q, and Real-Time Transport Protocol (RTP)
Video network features	Intelligent packet-loss recovery of video transmission
Network interface	<ul style="list-style-type: none">• One LAN or Ethernet (RJ-45); 100/1000 Mbps• Internal 4-port Ethernet switch with 2 Power over Ethernet plus (PoE+) (IEEE 802.3af) ports on Codec
Other interfaces	Web-based user interface; IP address assignment can be statically configured or configured through the Cisco TelePresence administrator web interface
Embedded encryption	Support for full media and signaling encryption for up to 48 segments
Scheduling services	Ability to offer email calendaring and scheduling services from a web-enabled application; to take advantage of this feature, you must install and configure the Cisco TelePresence Manager server to work with your calendar and email applications
Directory services	Ability to offer up to 40 favorites entries for convenient speed dialing or for integration into the Cisco Unified Communications Manager general directory service, which features a search function for thousands of directory entries

Ordering Information

Table 4 gives ordering information for the Cisco TelePresence TX1310.

Table 4. Ordering Information

Product Name	Part Number
Cisco TelePresence TX1310 65	CTS-TX1310-65
Ordering Options for the Cisco TelePresence TX1310	
Power cords	Select the appropriate power cord pair option to plug into the wall outlets in the country where the Cisco TelePresence system will be deployed.

Cisco Service and Support

Cisco and our partners provide a broad portfolio of smart, personalized services and support that can help you realize the full business value of your Cisco TelePresence investment by increasing business agility and network availability. This portfolio of services accelerates business innovation by harnessing the network as a powerful business platform. For more information about these services, visit:

<http://www.cisco.com/go/telepresenceservices>.

For More Information

For more information about the Cisco TelePresence TX1310, please visit <http://www.cisco.com/go/telepresence> or contact your local Cisco account representative or authorized Cisco partner.



Americas Headquarters
Cisco Systems, Inc.
San Jose, CA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV Amsterdam,
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: www.cisco.com/go/trademarks. Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)